Section 1. Identification

GHS product identifier: Product number:DTM 1600 Waterborne Urethane Primer
DTM 1600 Waterborne Urethane Primer

Product use:

Restrictions on use:

Manufacture/Supplier:

Address:

Surface Coating

None known

Precision Coatings

1940 E. Trafficway

Springfield, MO 65802

Telephone: 417-862-5738 **FAX:** 417-862-8874

Website: www.precisioncoatingsinc.com

Emergency telephone number: 800-424-9300 Chemtrec Contract CCN675735

Section 2. Hazards identification

OSHA/HCS status: This material is not classified as hazardous by the OSHA HazCom 2012 (29 CFR

1910.1200).

Hazard

classification: This material is not classified as hazardous by the OSHA HazCom 2012 (29 CFR

1910.1200).

Section 3. Composition / Information on Ingredients

There are no hazardous components above the relevant concentration limits according to OSHA HazCom 2012

OTHER INGREDIENTS

Components	CAS#	Percent
Titanium dioxide*	13463-67-7	0-20
Aluminum hydroxide*	21645-51-2	0-3
Silica dioxide, amorphous*	7631-86-9	0-3
Carbon black*	1333-86-4	0-3
Triethanolamine**	102-71-6	0.1-0.3
Polypropylene glycol	25322-69-4	0.1-0.3
2-butoxyethanol	111-76-2	0.1-0.3

^{*}Titanium dioxide; aluminum hydroxide; silica dioxide, amorphous and carbon black are bound within the polymer matrix. **Triethanolamine is a neutralizing agent that is bound within the polymer matrix as a salt.

Section 4. First aid measures

Eye Contact: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. In case of irritation form airborne exposure, move to fresh air. Get medical

attention if irritation develops.

Skin Contact: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes.

Continue to rinse for at least 10 minutes. Get medical attention if irritation develops. Wash

clothing before reuse. Clean shoes thoroughly before reuse.

Inhalation: If inhaled, remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give

artificial respiration. Get medical attention if irritation develops.

Ingestion: Do not induce vomiting. Wash out mouth with water. Remove dentures if any. Get medical

attention if symptoms occur. Never give anything by mouth to an unconscious person. If

unconscious, place in recovery position and get medical attention immediately.

Most important symptoms/effects,

Page 1 of 11

SDS Number: DTM 1600 Waterborne Urethane Primer

Version 01

<u>acute</u>

Potential acute health

<u>effects</u>

Eye contact: Causes eye irritation.

Skin contact: Causes skin irritation.

Inhalation: Not available

Ingestion: Not available

Over-exposure signs/symptoms

Eye contact: Adverse symptoms may include the following:

pain or irritation. Watering Redness

Skin contact: Adverse symptoms may include the following:

irritation redness

Inhalation: Not available

Ingestion: Adverse symptoms may include the following:

nausea or vomiting

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician: Not available

Specific treatments: Treat symptomatically and supportively.

Protection of first-

aiders: No action shall be taken involving any personal risk or without suitable training. It may be

dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Use dry chemical, carbon dioxide, water spray (fog) or foam.

Section 5. Fire-fighting measures

Suitable extinguishing media:

Unsuitable extinguishing

media:

Not available

Special hazards arising from

the substance or mixture:

Cool closed containers exposed to fire with water spray. Will not explode on

mechanical impact.

Hazardous thermal

decomposition products: Decomposition products may include the following materials:

carbon dioxide, carbon monoxide, smoke, oxides of nitrogen, formaldehyde,

silicone compounds.

Special protective actions for

fire-fighters:

Cool closed containers exposed to fire with water. Do not release runoff from

fire to drains or watercourses.

Page 2 of 11

SDS Number: DTM 1600 Waterborne Urethane Primer

Version 01 Revision Date: 05/26/2015

Special protective equipment for fire-fighters:

Fire-fighters should wear appropriate protective equipment and self contained breathing apparatus with full face piece operated in the positive pressure mode

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: Evacuate surrounding areas. Keep unnecessary and unprotected personnel

from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any

information in Section 8 on suitable and unsuitable materials. See also the

information in "For non-emergency personnel".

Environmental precautions: Avoid dispersal of spilled material and runoff and contact with soil, waterways,

drains and sewers. Inform the relevant authorities if the product has caused

environmental pollution (sewers, waterways, soil or air).

Methods and material for containment and cleaning up:

Eliminate sources of ignition. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Avoid runoff into storm sewers and ditches which lead to waterways. Use only non-combustible material for clean-up. Recover by pumping (use explosion proof or hand pump). Use clean, non-sparking tools to collect absorbed materials. Eliminate all ignition sources. Prevent additional discharge of material is able to do so safely. Do not touch or walk through spilled material. Collect spilled materials for disposal. Wear appropriate personal protective equipment (see Section 8 Exposure controls/personal protection). Evacuate unnecessary personnel.

Section 7. Handling and storage

Precautions for safe handling:

Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not swallow. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Empty containers retain product residue and can be hazardous. Do not reuse container. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas.

Conditions for safe storage, including any incompatibilities:

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Protect from freezing. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept

See also Section 8 for additional information on hygiene measures.

Page 3 of 11 SDS Number: DTM 1600 Waterborne Urethane Primer Version 01

upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls / personal protection

Control parameters

Occupational exposure limits

U.S. ACGIH Threshold Limit Values

Components	Type	Value	Form
Aluminum hydroxide	TWA	1 mg/m3	Respirable fraction
Titanium dioxide	TWA	10 mg/m3	
Triethanolamine	TWA	5mg/m3	
2-butoxyethanol	TWA	20ppm	

U.S. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

ComponentsTypeValueFormTitanium dioxidePEL15mg/m3Total dust

2-butoxyethanol PEL 50ppm, 240 mg/m3

U.S. OSHA Table Z-3 (29 CFR 1910.1000)

ComponentsTypeValueFormSilicon dioxideTWA0.8 mg/m320mppcf

Appropriate engineering

controls: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other

engineering controls to keep worker exposure to airborne contaminants below any

recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust

concentrations below any lower explosive limits.

Individual protection measures

Hygiene measures: Wash hands, forearms and face thoroughly after handling chemical products, before eating,

smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection: Safety glasses equipped with side shields are recommended as minimum protection in industrial

settings.

Skin protection

Hand protection: Chemical-resistant gloves complying with an approved standard should be worn at all times

when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any

glove material may be different for different glove manufacturers.

Body protection: Personal protective equipment for the body should be selected based on the task being

performed and the risks involved and should be approved by a specialist before handling this

product.

Other skin protection: Appropriate footwear and any additional skin protection measures should be selected based on

the task being performed and the risks involved and should be approved by a specialist before

handling this product.

Respiratory protection: Use a properly fitted, air-purifying or supplied-air respirator complying with an approved standard

if a risk assessment indicated this is necessary. Respirator selection must be based on known or

anticipated exposure levels, the hazards of the product and the safe working limits of the

selected respirator.

Page 4 of 11

SDS Number: DTM 1600 Waterborne Urethane Primer

Version 01

Section 9. Physical & Chemical Properties

Appearance

Physical state: Liquid Form: Liquid

Color: Milky to opaque

Odor: None

Odor threshold: Not available

pH: Not available

Melting point/freezing point: Not available

Initial boiling point and boiling

range: 98°C (208.4°F)

Flash point: Not applicable (water based product); however, solid

material will support combustion if water has been

evaporated.

Evaporation rate: Not available

Upper/lower flammability or

explosive limits:

Not available

Vapor pressure: Not available

Vapor density: \Rightarrow 1 Air = 1

Relative density: 1.00-1.9368

Solubility(ies): Not available

Partition coefficient: n-

octanol/water: Not available

Auto-ignition temperature: Not available

Decomposition temperature: Not available

Viscosity: Not available

VOC (mixed less water &

exempt compounds): Less than 50 grams/liter

Other information: No additional information

Section 10. Chemical stability & reactivity information

Reactivity: None known.

Chemical stability: Stable.

Possibility of hazardous

reactions: None known.

Page 5 of 11

SDS Number: DTM 1600 Waterborne Urethane Primer

Version 01

Conditions to avoid: Water reactives

Incompatible materials: Strong oxidizing agents. Strong acids. Strong alkalis.

Hazardous decomposition

products:

Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

Section 11. Toxicological information

Information on toxicological

effects

Acute toxicity

Conclusion/summary: Not available

Oral: Not available

Dermal: Not available

Inhalation: Not available

Irritation/Corrosion

Skin: Not available

Eyes: Not available

Respiratory: Not available

Sensitization

Skin: Not available

Respiratory: Not available

Mutagenicity

Conclusion/Summary: Not available

Carcinogenicity

Conclusion/Summary: Titanium dioxide: In lifetime inhalation studies rats were exposed for 2 years to

respectively 10, 50 and 250 mg/m3 of respirable TiO2. Slight lung fibrosis was observed at 50 and 250 mg/m3 levels. Microscopic lung tumors were also observed in 13 percent of the rats exposed to 250 mg/m3, an exposure level that caused lung overloading and impairment of rat lungs clearance mechanisms. In further studies, these tumors were found to occur only under particle overload conditions in a uniquely sensitive species, the rat, and have little or no relevance for humans. The pulmonary inflammatory response to TiO2 particles exposure was also found to be much more severe in rats than in other rodent species. In February 2006, IARC has re-evaluated Titanium dioxide as pertaining to Group 2B: "possibly carcinogenic to humans", based upon inadequate evidence in humans and sufficient evidence in experimental animals for the carcinogenicity of titanium dioxide. IARC evaluation guidelines consider the generation of tumors, in 2 different studies within the same animal species, to be adequate criteria for an assessment of sufficient evidence.

The conclusions of several epidemiology studies on more than 20000 TiO2 industry workers in Europe and the USA did not suggest a carcinogenic effect of

Page 6 of 11

SDS Number: DTM 1600 Waterborne Urethane Primer Version 01

Version 01 Revision Date: 05/26/2015

TiO2 dust on the human lung. Mortality from other chronic diseases, including other respiratory diseases, was also not associated with exposure to TiO2 dust. Based upon all available study results, DuPont scientists conclude that titanium dioxide will not cause lung cancer or chronic respiratory diseases in humans at concentrations experienced in the workplace.

Carbon black:

ANIMAL TOXICITY:

Rat, oral, duration 2 years Effect: no tumors.

Mouse, oral, duration 2 years Effect: no tumors.

Rat, inhalation, duration 2 years

Target organ: lungs.

Effect: inflammation, fibrosis, tumors.

Note: Tumors in the rat lung are considered to be related to the "lung overload" rather than to a specific chemical effect of carbon black itself in the lung. These effects in rats have been reported in many studies on other poorly soluble inorganic particles and appear to be rat specific (ILSI, 2000). Tumors have not been observed in other species (i.e., mouse and hamster) for carbon black or other poorly soluble particles under similar circumstances and study conditions.

MORTALITY STUDIES (HUMAN DATA):

A study on carbon black production workers in the UK (Sorahan, 2001) found an increased risk of lung cancer in two of the five plants studied; however, the increase was not related to the dose of carbon black. Thus, the authors did not consider the increased risk in lung cancer to be due to carbon black exposure. A German study of carbon black workers at one plant (Morfeld, 2006; Buechte, 2006) found a similar increase in lung cancer risk but, like the Sorahan, 2001 (UK study), found no association with carbon black exposure. A large US study of 18 plants showed a reduction in lung cancer risk in carbon black production workers (Dell, 2006). Based upon these studies, the February 2006 Working Group at the International Agency for Research on Cancer (IARC) concluded that the human evidence for carcinogenicity was inadequate (IARC, 2010).

Since the IARC evaluation of carbon black, Sorahan and Harrington (2007) have re-analyzed the UK study data using an alternative exposure hypothesis and found a positive association with carbon black exposure in two of the five plants. The same exposure hypothesis was applied by Morfeld and McCunney (2009) to the German cohort; in contrast, they found no association between carbon black exposure and lung cancer risk and, thus, no support for the alternative exposure hypothesis used by Sorahan and Harrington.

Over, as a result of these detailed investigations, no causative link between carbon black exposure and cancer risk in humans has been demonstrated.

IARC CANCER CLASSIFICATION:

In 2006 IARC re-affirmed its 1995 finding that there is "inadequate evidence" from human health studies to assess whether carbon black causes cancer in humans. IARC concluded that there is "sufficient

Page 7 of 11 SDS Number: DTM 1600 Waterborne Urethane Primer Version 01

evidence" in experimental animal studies for the carcinogenicity of carbon black. IARC's overall evaluation is that carbon black is "possibly carcinogenic to humans (Group 2B)". This conclusion was based on IARC's guidelines, which generally require such a classification if one species exhibits carcinogenicity in two or more animal studies (IARC, 2010).

Solvent extracts of carbon black were used in one study of rats in which skin tumors were found after dermal application and several studies of mice in which sarcomas were found following subcutaneous injection. IARC concluded that there was "sufficient evidence" that carbon black extracts can cause cancer in animals (Group 2B).

ACGIH CANCER CLASSIFICATION:

Confirmed Animal Carcinogen with Unknown Relevance to Humans (Category A3 Carcinogen).

Reproductive toxicity

Not available **Conclusion/Summary:**

Specific target organ toxicity

(single exposure):

Not available

Specific target organ toxicity

(repeated exposure):

Not available

Not available

Aspiration hazard:

Information on likely routes of

exposure:

Eye contact:

Routes of entry anticipated: Oral, Dermal, Inhalation.

Potential acute health effects:

Causes eye irritation.

Not available

Inhalation:

Causes skin irritation. Skin contact:

Ingestion:

Not available

Symptoms related to the physical, chemical and toxicological characteristics

Adverse symptoms may include pain or irritation, watering, redness.

Eye contact: Not available

Inhalation:

Adverse symptoms may include irritation, redness.

Skin contact: Adverse symptoms may include nausea or vomiting.

Ingestion:

Potential chronic health Not available

effects:

Page 8 of 11 SDS Number: DTM 1600 Waterborne Urethane Primer Version 01

Section 12. Ecological information

Toxicity

Acute toxicity

Fish Broduct

Product: Not available

Specified substances: Not available

Aquatic invertebrates

Product: Not available

Chronic toxicity

Fish Not available Product:

Aquatic invertebrates Not available

Product:

Toxicity to aquatic plants

Not available

Product:

Specified substances: Not available

Persistence and degradability

Biodegradation

Product: Not available

Specified substances:

Biological Oxygen Demand

Product: Not available

Specified substances: Not available

Chemical Oxygen Demand

Product: Not available

Specified substances: Not available

BOD/COD ratio: Not available

Bioaccumulative potential: Not available

Mobility in soil: Not available

Results of PBT and vPvB assessment: Not available

Other adverse effects: Not available

Section 13. Disposal considerations

Disposal methods: Dispose of waste in accordance with all local, state and federal regulations.

Not available

Section 14. Transport information

DOT

Basic shipping requirements: Non-Regulated

IATA

Basic shipping requirements: Non-Regulated

Page 9 of 11

SDS Number: DTM 1600 Waterborne Urethane Primer

Version 01

IMDG

Basic shipping requirements Non-Regulated

Section 15. Regulatory information

US federal regulations

OSHA: There are no hazardous components above the relevant concentration limits

according to OSHA HazCom 2012 (29 CFR 1910.1200).

SARA Title III Section 313 - Toxic

Chemical: Listed

Substance: 2-butoxyethanol

SARA Title III Section 302 Extremely

hazardous substances: None

SARA Title III Section 311/312 Hazard

categories: Non-hazardous under Section 311/312

Inventory Status

Country(s) or region	Inventory name	On inventory (yes/no)*	
Australia	Australian Inventory of Chemical Substances (AICS)		Yes
Canada	Domestic Substances List (DSL)		Yes
China	Inventory of Existing Chemical Substances in China (IECSC)		Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)		Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)		Yes
Korea	Existing Chemicals List (ECL)		Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)		Yes
United States & Puerto	Toxic Substances Control Act (TSCA) Inventory		Yes

^{*} A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State Regulations

65:

California Proposition

This product does not contain chemicals known to the State of California to cause cancer.

This product does not contain chemicals known to the State of California to cause birth defects or other

reproductive harm.

Massachusetts RTK: Silicon dioxide (CAS 7631-86-9)

Titanium Dioxide (CAS 13463-67-7) 2,2',2"-Nitrilotriethanol (CAS 102-71-6) 2-butoxyethanol (CAS 111-76-2) 2-Propanamine,N-ethyl-N(1-methylethyl)-

New Jersey RTK: Silicon dioxide (CAS 7631-86-9)

Titanium Dioxide (CAS 13463-67-7) 2,2',2"-Nitrilotriethanol (CAS 102-71-6) Polypropylene glycol (CAS 25322-69-4) 2-butoxyethanol (CAS 111-76-2) 2-Propanamine,N-ethyl-N(1-methylethyl)-

Pennsylvania RTK: Silicon dioxide (CAS 7631-86-9)

Titanium Dioxide (CAS 13463-67-7) 2,2',2"-Nitrilotriethanol (CAS 102-71-6) Polypropylene glycol (CAS 25322-69-4) 2-butoxyethanol (CAS 111-76-2) 2-Propanamine,N-ethyl-N(1-methylethyl)-

Section 16. Other Information

Page 10 of 11

SDS Number: DTM 1600 Waterborne Urethane Primer

Version 01

Further

information HMIS® is a registered trade and service mark of the NPCA

HMIS®

ratings Health: 1

Flammability: 0 Physical hazard: 0

NFPA ratings Health: 1

Flammability: 0 Instability: 0

Disclaimer

The information on this SDS was obtained from sources which we believe to be reliable. However, the information provided is without warranty, expressed or implied, regarding its correctness. Some of the information presented and conclusions drawn herein are from sources other than direct test data on the product itself. The information and recommendations are offered for the user's consideration and examination and should be used to make independent determination of the methods to safeguard workers and the environment. The conditions or methods of handling storage, use and disposal of the product are beyond our control and may beyond our control and may be beyond our knowledge. For these reasons we do not assume responsibility and expressly disclaim any liability for loss, damage, or expense arising out of or in any way connected with handling, storage, use or disposal of this product. It is the responsibility of the user to comply with all Federal, State and Local laws and regulations.

Issue date 05/26/2015

Version 01 Revision Date: 05/26/2015