



12030 **Urethane Accelerator**

DESCRIPTION

12030 Urethane Accelerator is a catalyst designed to accelerate the drying and cure times of PC3v100, PC3, PC4 and Reflect 3000 Topcoats and Clear Coats. This additive maintains excellent pot life stability while producing fast tack free and curing times.

TECHNICAL DATA

PACKAGED VOC	107 g/l, 0.89 lbs./gal
VOC AS USED AS DIRECTED	979 g/l, 8.16 lbs./gal
SHELF LIFE	one year (unopened)
FLASH POINT	-4° F, -20° C
RECOMMENDED DILUTION FOR USE	8 fluid ounces per gallon of activated Topcoat or Clear Coat

DIRECTIONS FOR USE

Add up to 8 fluid ounces of 12030 Urethane Accelerator per activated gallon of Topcoat Clear

DISCLAIMER: The technical information and suggestions for use have been compiled for your guidance and usage. Such information is based on Precision Coatings' experience and research and is believed to be reliable. As Precision Coatings has no control over conditions in which the product is used, stored, or otherwise handled, the above information does not constitute a warranty. Buyers must assume responsibility for the suitability of the product for their purposes.

10.2016

PRECISION COATINGS

1940 E. Trafficway, Springfield, MO 65802

417.862.5738

www.precisioncoatingsinc.com