



16070 **Urethane Retarder**

DESCRIPTION

Precision Coatings Urethane Retarder (16070) is a solvent retarder designed for use during hot and humid weather conditions. Precision's Urethane Retarder is used in conjunction with Precision PC3 Series Acrylic Polyurethane Topcoats, PC4 Acrylic Polyurethane Topcoats and PC5 Polysiloxane Topcoats. Urethane Retarder (16070):

- Increases wet edge times and
- Retains excellent appearance of topcoat

TECHNICAL DATA

PACKAGED VOC	810 grams/liter
POT LIFE OF MIXED GALLON	3 hours @70° F (21° C)
SHELF LIFE	one year (unopened)
FLASH POINT	102° F (39° C)
RECOMMENDED USE LEVEL	Add 6 to 12 fluid ounces per activated gallon

DIRECTIONS FOR USE

Add 6 to 12 fluid ounces of Urethane Retarder (16070) per activated gallon of PC3 Acrylic Polyurethane Topcoat, PC4 Acrylic Polyurethane Topcoat and PC5 Polysiloxane Topcoat.

DISCLAIMER: The technical information and suggestions for use have been compiled for your guidance and usage. Such information is based on Precision Coatings' experience and research and is believed to be reliable. As Precision Coatings has no control over conditions in which the product is used, stored, or otherwise handled, the above information does not constitute a warranty. Buyers must assume responsibility for the suitability of the product for their purposes.

10.2016

PRECISION COATINGS

1940 E. Trafficway, Springfield, MO 65802

417.862.5738

www.precisioncoatingsinc.com